Linear · PDX SERIES White 5000K

lumher

24 V
DC

MASTER
SLAVE

CASCADABLE

90 mm
INCREMENTAL

CABLE
M12A

MACHINE VISION

CONTINUOUS 1x
STROBE 4x

INTEGRATED
CONTROLLER

POLARIZED

IP40
IP65

36
MONTHS

EU
MADE IN SPAIN

Technical specifications

Power supply voltage	24 Vdc ±5%	
Trigger input	24 Vdc PNP / NPN	
Max. on time	Continuous = unlimited	Strobe = 10 ms
Max. working cycle	Continuous = 1	Strobe = 1/6
Max. consumption Trigger input	1,5 mA	
Max. number of cascadable modules	Power = 48	Strobe = 12
Wavelength	White	5000 K
Beam angle	Semidiffuse Ultradiffuse	60° 110°
Electrical protections	Transient overvoltages Polarity reversal Current sabilizer	YES YES YES
IP Rating	IP40 o IP65	
Protection type	Class III	
Operating temperature	-10°C to +40°C	
Storage temperature	0°C to +60 °C	
Max. relative humidity	80% (without condensation)	
Body material	Anodized aluminum	
Side cover material	Anodized aluminum	
Diffuser material	Polycarbonate	
Connection types	M12A, 2m cable, M12A connector with cable	
Standards	RoHs, CE	

(1) The number representing the length of the luminaire is the number of modules it has.

Connection

M12A input - Cable	Continuous	Master Continuous - Strobe	Slave Continuous - Strobe
Pin 1 - Brown	+24 Vdc	+24 Vdc	+24 Vdc
Pin 2 - White	Not connected	Trigger NPN	Not connected
Pin 3 - Blue	0 Vdc	0 Vdc	0 Vdc
Pin 4 - Black	Not connected	Trigger PNP	Signal IN - a

M12A output	Continuous	Master Continuous - Strobe	Slave Continuous - Strobe
Pin 1 - Brown	+24 Vdc	+24 Vdc	+24 Vdc
Pin 2 - White	Not connected	Not connected	Not connected
Pin 3 - Blue	0 Vdc	0 Vdc	0 Vdc
Pin 4 - Black	Not connected	Signal OUT - a	Signal OUT - a

M12A Male

M12A Female



Fixings

P00G1 , P00G2, P00G3, P00R1, P00R2, P00R3, P00R4, M6D16

PDX · 5000K

lumher

Measures

IP40

M12A axial version



M12A radial version



IP65

M12A axial version



M12A radial version



Measures in mm

Selection guide

PDX D

Output
- Y - M12A axial female connector
- YL - M12A radial female connector
- PY - 10 cm axial cable with M12A female connector
- RY - 10 cm radial cable with M12A female connector

Input
- K - Axial Cable, 2 m
- KL - Radial Cable, 2 m
- Y - M12A axial male connector
- YL - M12A radial male connector
- PY - 10 cm axial cable with M12A male connector
- RY - 10 cm radial cable with M12A male connector

Cover
- C - Semidiffuse
- U - Ultradiffuse
- M - Semidiffuse Polarized
- G - Ultradiffuse Polarized

IP Rating
- 3 - IP40
- 5 - IP65

Working mode
- P - Continuous
- Z - Master Cont. - Strobe
- X - Slave Cont. - Strobe

Length
- 1 - 15 - 90 mm steps

PDX · 5000K

lumher

Model PDX · White 5000K

PDX

5000K
WHITE

SEMIDIFFUSE 60°

ULTRADIFFUSE 110°

PHOTOBIOLOGICAL RISK
RG1 - LOW

60.000h
LIFESPAN

Table of characteristics

	Length L1 (2) (mm)	Length L2 (2) (mm)	Weight (g)	Luminous flux (3) (lm) CONT.	Luminous flux (3) (lm) STROBE	Power consumed (W) CONT.	Power consumed (W) STROBE
PDX 01...	120	138	97	304	1.216	1,9	7,6
PDX 02...	210	228	145	608	2.432	3,8	15,2
PDX 03...	300	318	193	912	3.648	5,7	22,8
PDX 04...	390	408	241	1.216	4.864	7,6	30,4
PDX 05...	480	498	289	1.520	6.080	9,5	38,0
PDX 06...	570	588	337	1.824	7.296	11,4	45,6
PDX 07...	660	678	385	2.128	8.512	13,3	53,2
PDX 08...	750	768	433	2.432	9.728	15,2	60,8
PDX 09...	840	858	481	2.736	10.944	17,1	68,4
PDX 10...	930	948	529	3.040	12.160	19,0	76,0
PDX 11...	1.020	1.038	577	3.344	13.376	20,9	83,6
PDX 12...	1.110	1.128	625	3.648	14.592	22,8	91,2
PDX 13...	1.200	1.218	673	3.952	-	24,7	-
PDX 14...	1.290	1.308	721	4.256	-	26,6	-
PDX 15...	1.380	1.398	769	4.560	-	28,5	-

(2) Versions with radial input and/or outlet will have length L2, the rest will be L1.
(3) The luminous flux (lm) is before diffuser.

lumher